

```

<?xml version="1.0" encoding="UTF-8"?>
<definitions xmlns="http://schemas.xmlsoap.org/wsdl/"
    xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
    xmlns:xsdLocall="http://www.siebel.com/xml/Account_EMR"
    targetNamespace="http://siebel.com/asi/"
    xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
    xmlns:xsd="http://www.w3.org/2001/XMLSchema"
    xmlns:tns="http://siebel.com/asi/">

<types>
    <xsd:schema elementFormDefault="qualified"
        attributeFormDefault="unqualified"
        targetNamespace="http://siebel.com/webservices"
        xmlns:xsd="http://www.w3.org/2001/XMLSchema"
        xmlns="http://siebel.com/webservices">
        <xsd:element name="UsernameToken" type="xsd:string"/>
        <xsd:element name="PasswordText" type="xsd:string"/>
        <xsd:element name="SessionType" type="xsd:string"/>
        <xsd:element name="SessionToken" type="xsd:string"/>
    </xsd:schema>
    <xsd:schema elementFormDefault="qualified"
        attributeFormDefault="unqualified"
        xmlns:xsdLocall="http://www.siebel.com/xml/Account_EMR"
        targetNamespace="http://www.siebel.com/xml/Account_EMR"
        xmlns:xsd="http://www.w3.org/2001/XMLSchema">
        <xsd:annotation>
            <xsd:documentation>Copyright (C) 2001-2004 Siebel Systems, Inc. All
                rights reserved. Siebel XSD Generation</xsd:documentation>
        </xsd:annotation>
        <xsd:element name="ListOfAccount" type="xsdLocall:ListOfAccount"></xsd:element>
        <xsd:complexType name="ListOfAccountTopElmt">
            <xsd:sequence>
                <xsd:element name="ListOfAccount" maxOccurs="1" minOccurs="1"
                    type="xsdLocall:ListOfAccount"></xsd:element>
            </xsd:sequence>
        </xsd:complexType>
        <xsd:complexType name="ListOfAccount">
            <xsd:sequence>
                <xsd:element name="Account" maxOccurs="unbounded" minOccurs="0"
                    type="xsdLocall:Account"></xsd:element>
            </xsd:sequence>
        </xsd:complexType>
        <xsd:complexType name="Account">
            <xsd:sequence>
                <xsd:element name="AccountId" maxOccurs="1" minOccurs="0"
                    type="xsdLocall:string30"></xsd:element>
                <xsd:element name="AccountStatus" maxOccurs="1" minOccurs="0"
                    type="xsdLocall:string24"></xsd:element>
                <xsd:element name="Alias" maxOccurs="1" minOccurs="0"
                    type="xsdLocall:string50"></xsd:element>
                <xsd:element name="CurrencyCode" maxOccurs="1" minOccurs="0"
                    type="xsdLocall:string15"></xsd:element>
                <xsd:element name="IntegrationId" maxOccurs="1" minOccurs="0"
                    type="xsdLocall:string30"></xsd:element>
                <xsd:element name="Location" maxOccurs="1" minOccurs="0"

```

```

        type="xsdLocal1:string50">></xsd:element>
<xsd:element name="Name" maxOccurs="1" minOccurs="0"
            type="xsdLocal1:string100">></xsd:element>
<xsd:element name="ParentAccountId" maxOccurs="1" minOccurs="0"
            type="xsd:string">></xsd:element>
<xsd:element name="ParentAccountIntegrationId" maxOccurs="1"
            minOccurs="0" type="xsdLocal1:string30">></xsd:element>
<xsd:element name="ParentAccountLocation" maxOccurs="1" minOccurs="0"
            type="xsdLocal1:string50">></xsd:element>
<xsd:element name="ParentAccountName" maxOccurs="1" minOccurs="0"
            type="xsdLocal1:string100">></xsd:element>
<xsd:element name="PrimaryOrganization" maxOccurs="1" minOccurs="0"
            type="xsdLocal1:string100">></xsd:element>
<xsd:element name="ModId" maxOccurs="1" minOccurs="0"
            type="xsdLocal1:string30">></xsd:element>
<xsd:element name="ListOfRelatedContact" maxOccurs="1" minOccurs="0"
            type="xsdLocal1:ListOfRelatedContact">></xsd:element>
<xsd:element name="ListOfRelatedOpportunity" maxOccurs="1"
            minOccurs="0" type="xsdLocal1:ListOfRelatedOpportunity">></xsd:element>
<xsd:element name="ListOfRelatedServiceRequest" maxOccurs="1"
            minOccurs="0"
            type="xsdLocal1:ListOfRelatedServiceRequest">></xsd:element>
</xsd:sequence>
<xsd:attribute name="operation" type="xsd:string">></xsd:attribute>
</xsd:complexType>
<xsd:complexType name="ListOfRelatedContact">
    <xsd:sequence>
        <xsd:element name="RelatedContact" maxOccurs="unbounded" minOccurs="0"
                    type="xsdLocal1:RelatedContact">></xsd:element>
    </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="RelatedContact">
    <xsd:sequence>
        <xsd:element name="ContactId" maxOccurs="1" minOccurs="0"
                    type="xsdLocal1:string30">></xsd:element>
        <xsd:element name="FirstName" maxOccurs="1" minOccurs="0"
                    type="xsdLocal1:string50">></xsd:element>
        <xsd:element name="ContactIntegrationId" maxOccurs="1" minOccurs="0"
                    type="xsdLocal1:string30">></xsd:element>
        <xsd:element name="LastName" maxOccurs="1" minOccurs="0"
                    type="xsdLocal1:string50">></xsd:element>
        <xsd:element name="MiddleName" maxOccurs="1" minOccurs="0"
                    type="xsdLocal1:string50">></xsd:element>
        <xsd:element name="PersonUID" maxOccurs="1" minOccurs="0"
                    type="xsdLocal1:string100">></xsd:element>
        <xsd:element name="PrimaryOrganization" maxOccurs="1" minOccurs="0"
                    type="xsdLocal1:string100">></xsd:element>
        <xsd:element name="ModId" maxOccurs="1" minOccurs="0"
                    type="xsdLocal1:string30">></xsd:element>
    </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="ListOfRelatedOpportunity">
    <xsd:sequence>
        <xsd:element name="RelatedOpportunity" maxOccurs="unbounded"

```

```

        minOccurs="0" type="xsdLocal1:RelatedOpportunity">></xsd:element>
    </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="RelatedOpportunity">
    <xsd:sequence>
        <xsd:element name="Id" maxOccurs="1" minOccurs="0"
                    type="xsdLocal1:string30"></xsd:element>
        <xsd:element name="Created" maxOccurs="1" minOccurs="0"
                    type="xsdLocal1:string30"></xsd:element>
        <xsd:element name="ModId" maxOccurs="1" minOccurs="0"
                    type="xsdLocal1:string30"></xsd:element>
        <xsd:element name="Account2" maxOccurs="1" minOccurs="0"
                    type="xsdLocal1:string100"></xsd:element>
        <xsd:element name="AccountId" maxOccurs="1" minOccurs="0"
                    type="xsd:string"></xsd:element>
        <xsd:element name="AccountIntegrationId" maxOccurs="1" minOccurs="0"
                    type="xsdLocal1:string30"></xsd:element>
        <xsd:element name="AccountLocation" maxOccurs="1" minOccurs="0"
                    type="xsdLocal1:string50"></xsd:element>
        <xsd:element name="CreatedBy Name" maxOccurs="1" minOccurs="0"
                    type="xsdLocal1:string50"></xsd:element>
        <xsd:element name="CurrencyCode" maxOccurs="1" minOccurs="1"
                    type="xsdLocal1:string15"></xsd:element>
        <xsd:element name="Description" maxOccurs="1" minOccurs="0"
                    type="xsdLocal1:string255"></xsd:element>
        <xsd:element name="KeyContactFirstName" maxOccurs="1" minOccurs="0"
                    type="xsdLocal1:string50"></xsd:element>
        <xsd:element name="KeyContactId" maxOccurs="1" minOccurs="0"
                    type="xsd:string"></xsd:element>
        <xsd:element name="KeyContactLastName" maxOccurs="1" minOccurs="0"
                    type="xsdLocal1:string50"></xsd:element>
        <xsd:element name="KeyContactMiddleName" maxOccurs="1" minOccurs="0"
                    type="xsdLocal1:string50"></xsd:element>
        <xsd:element name="Name" maxOccurs="1" minOccurs="1"
                    type="xsdLocal1:string100"></xsd:element>
        <xsd:element name="OpptyId" maxOccurs="1" minOccurs="0"
                    type="xsd:string"></xsd:element>
        <xsd:element name="ParentOpportunityId" maxOccurs="1" minOccurs="0"
                    type="xsd:string"></xsd:element>
        <xsd:element name="ParentOpportunityName" maxOccurs="1" minOccurs="0"
                    type="xsdLocal1:string100"></xsd:element>
    </xsd:sequence>
    <xsd:attribute name="operation" type="xsd:string"></xsd:attribute>
    <xsd:attribute name="searchspec" type="xsd:string"></xsd:attribute>
</xsd:complexType>
<xsd:complexType name="ListOfRelatedServiceRequest">
    <xsd:sequence>
        <xsd:element name="RelatedServiceRequest" maxOccurs="unbounded"
                    minOccurs="0" type="xsdLocal1:RelatedServiceRequest"></xsd:element>
    </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="RelatedServiceRequest">
    <xsd:sequence>
        <xsd:element name="Id" maxOccurs="1" minOccurs="0"

```

```

        type="xsdLocal1:string30">></xsd:element>
<xsd:element name="Created" maxOccurs="1" minOccurs="0"
             type="xsdLocal1:string30">></xsd:element>
<xsd:element name="ModId" maxOccurs="1" minOccurs="0"
             type="xsdLocal1:string30">></xsd:element>
<xsd:element name="Abstract" maxOccurs="1" minOccurs="0"
             type="xsdLocal1:string100">></xsd:element>
<xsd:element name="Account2" maxOccurs="1" minOccurs="0"
             type="xsdLocal1:string100">></xsd:element>
<xsd:element name="AccountComment" maxOccurs="1" minOccurs="0"
             type="xsdLocal1:string255">></xsd:element>
<xsd:element name="AccountId" maxOccurs="1" minOccurs="0"
             type="xsd:string">></xsd:element>
<xsd:element name="AccountIntegrationId" maxOccurs="1" minOccurs="0"
             type="xsdLocal1:string30">></xsd:element>
<xsd:element name="AccountLocation" maxOccurs="1" minOccurs="0"
             type="xsdLocal1:string50">></xsd:element>
<xsd:element name="AccountStatus2" maxOccurs="1" minOccurs="0"
             type="xsdLocal1:string30">></xsd:element>
<xsd:element name="ContactAccount" maxOccurs="1" minOccurs="0"
             type="xsdLocal1:string100">></xsd:element>
<xsd:element name="ContactAccountId" maxOccurs="1" minOccurs="0"
             type="xsd:string">></xsd:element>
<xsd:element name="ContactFirstName" maxOccurs="1" minOccurs="0"
             type="xsdLocal1:string50">></xsd:element>
<xsd:element name="ContactFullName" maxOccurs="1" minOccurs="0"
             type="xsd:string">></xsd:element>
<xsd:element name="ContactId" maxOccurs="1" minOccurs="0"
             type="xsd:string">></xsd:element>
<xsd:element name="ContactLastName" maxOccurs="1" minOccurs="0"
             type="xsdLocal1:string50">></xsd:element>
<xsd:element name="CreatedByByName" maxOccurs="1" minOccurs="0"
             type="xsdLocal1:string50">></xsd:element>
<xsd:element name="Description2" maxOccurs="1" minOccurs="0"
             type="xsdLocal1:string2000">></xsd:element>
<xsd:element name="ParentSRAbstract" maxOccurs="1" minOccurs="0"
             type="xsdLocal1:string100">></xsd:element>
<xsd:element name="ParentSRNumber" maxOccurs="1" minOccurs="0"
             type="xsdLocal1:string64">></xsd:element>
<xsd:element name="ParentServiceRequestId" maxOccurs="1" minOccurs="0"
             type="xsd:string">></xsd:element>
<xsd:element name="Priority" maxOccurs="1" minOccurs="0"
             type="xsdLocal1:string30">></xsd:element>
<xsd:element name="ProjectId" maxOccurs="1" minOccurs="0"
             type="xsd:string">></xsd:element>
<xsd:element name="ProjectName" maxOccurs="1" minOccurs="0"
             type="xsdLocal1:string100">></xsd:element>
<xsd:element name="SRImpact" maxOccurs="1" minOccurs="0"
             type="xsdLocal1:string30">></xsd:element>
<xsd:element name="SRNumber" maxOccurs="1" minOccurs="0"
             type="xsdLocal1:string64">></xsd:element>
<xsd:element name="SRRootcause" maxOccurs="1" minOccurs="0"
             type="xsdLocal1:string30">></xsd:element>
<xsd:element name="SRTyp

```

```

        type="xsdLocal1:string30"></xsd:element>
    <xsd:element name="SRUrgency" maxOccurs="1" minOccurs="0"
        type="xsdLocal1:string30"></xsd:element>
    <xsd:element name="SerialNumber" maxOccurs="1" minOccurs="0"
        type="xsdLocal1:string100"></xsd:element>
    <xsd:element name="Severity" maxOccurs="1" minOccurs="0"
        type="xsdLocal1:string30"></xsd:element>
    <xsd:element name="Source" maxOccurs="1" minOccurs="0"
        type="xsdLocal1:string30"></xsd:element>
    <xsd:element name="Status" maxOccurs="1" minOccurs="1"
        type="xsdLocal1:string30"></xsd:element>
    <xsd:element name="Sub-Area" maxOccurs="1" minOccurs="0"
        type="xsdLocal1:string30"></xsd:element>
    <xsd:element name="Sub-Status" maxOccurs="1" minOccurs="1"
        type="xsdLocal1:string30"></xsd:element>
    <xsd:element name="Type" maxOccurs="1" minOccurs="0"
        type="xsdLocal1:string30"></xsd:element>
</xsd:sequence>
<xsd:attribute name="operation" type="xsd:string"></xsd:attribute>
<xsd:attribute name="searchspec" type="xsd:string"></xsd:attribute>
</xsd:complexType>
<xsd:simpleType name="string2000">
    <xsd:restriction base="xsd:string">
        <xsd:maxLength value="2000"></xsd:maxLength>
    </xsd:restriction>
</xsd:simpleType>
<xsd:simpleType name="string50">
    <xsd:restriction base="xsd:string">
        <xsd:maxLength value="50"></xsd:maxLength>
    </xsd:restriction>
</xsd:simpleType>
<xsd:simpleType name="string24">
    <xsd:restriction base="xsd:string">
        <xsd:maxLength value="24"></xsd:maxLength>
    </xsd:restriction>
</xsd:simpleType>
<xsd:simpleType name="string64">
    <xsd:restriction base="xsd:string">
        <xsd:maxLength value="64"></xsd:maxLength>
    </xsd:restriction>
</xsd:simpleType>
<xsd:simpleType name="string255">
    <xsd:restriction base="xsd:string">
        <xsd:maxLength value="255"></xsd:maxLength>
    </xsd:restriction>
</xsd:simpleType>
<xsd:simpleType name="string15">
    <xsd:restriction base="xsd:string">
        <xsd:maxLength value="15"></xsd:maxLength>
    </xsd:restriction>
</xsd:simpleType>
<xsd:simpleType name="string30">
    <xsd:restriction base="xsd:string">
        <xsd:maxLength value="30"></xsd:maxLength>

```

```

        </xsd:restriction>
    </xsd:simpleType>
    <xsd:simpleType name="string100">
        <xsd:restriction base="xsd:string">
            <xsd:maxLength value="100"></xsd:maxLength>
        </xsd:restriction>
    </xsd:simpleType>
</xsd:schema>
<xsd:schema elementFormDefault="qualified"
    attributeFormDefault="unqualified"
    targetNamespace="http://siebel.com/asi/"
    xmlns:xsd="http://www.w3.org/2001/XMLSchema">
<xsd:import namespace="http://www.siebel.com/xml/Account_EMR"></xsd:import>
<xsd:element name="AccountQueryPageMSO_Input">
    <xsd:complexType>
        <xsd:sequence>
            <xsd:element name="PageSize" type="xsd:string"></xsd:element>
            <xsd:element ref="xsdLocal1:ListOfAccount"></xsd:element>
            <xsd:element name="ViewMode" type="xsd:string"></xsd:element>
            <xsd:element name="StartRowNum" type="xsd:string"></xsd:element>
        </xsd:sequence>
    </xsd:complexType>
</xsd:element>
<xsd:element name="AccountQueryPageMSO_Output">
    <xsd:complexType>
        <xsd:sequence>
            <xsd:element ref="xsdLocal1:ListOfAccount"></xsd:element>
        </xsd:sequence>
    </xsd:complexType>
</xsd:element>
</xsd:schema>
</types>

<message name="SiebelInputHeaderMessage">
    <part name="userName" element="seblService:UsernameToken"/>
    <part name="passWord" element="seblService:PasswordText"/>
    <part name="SessionType" element="seblService:SessionType"/>
    <part name="SessionToken" element="seblService:SessionToken"/>
</message>

<message name="AccountQueryPageMSO_Input">
    <part name="AccountQueryPageMSO_Input"
        element="tns:AccountQueryPageMSO_Input"></part>
</message>
<message name="AccountQueryPageMSO_Output">
    <part name="AccountQueryPageMSO_Output"
        element="tns:AccountQueryPageMSO_Output"></part>
</message>
<portType name="AccountWSPort">
    <operation name="AccountQueryPageMSO">
        <input message="tns:AccountQueryPageMSO_Input"></input>
        <output message="tns:AccountQueryPageMSO_Output"></output>
    </operation>

```

```

</portType>
<binding name="AccountWSPort" type="tns:AccountWSPort">
    <soap:binding transport="http://schemas.xmlsoap.org/soap/http"
                  style="document"></soap:binding>
    <operation name="AccountQueryPageMSO">
        <soap:operation
            soapAction="document/http://siebel.com/asi/:AccountQueryPageMSO"></soap:operation>
        <soap:operation
            soapAction="document/http://siebel.com/asi:SNI_spcUpdate_spcOrder_spcFrom_spcSource"></soap:operation>
        <soap:header message="tns:SiebelInputHeaderMessage" part="userName" use="literal"/>
        <soap:header message="tns:SiebelInputHeaderMessage" part="passWord" use="literal"/>
        <soap:header message="tns:SiebelInputHeaderMessage" part="SessionType" use="literal"/>
        <soap:header message="tns:SiebelInputHeaderMessage" part="SessionToken" use="literal"/>
        <input>
            <soap:body use="literal"></soap:body>
        </input>
        <output>
            <soap:body use="literal"></soap:body>
        </output>
    </operation>
</binding>
<service name="AccountWS">
    <port binding="tns:AccountWSPort" name="AccountWSPort">
        <soap:address
location="http://&lt;webserver>/eai_&lt;lang>/start.swe?SWEExtSource=SecureWebService&amp;SWEExtC
md=Execute&amp;WSSOAP=1"></soap:address>
    </port>
</service>
</definitions>

```